MATERIAL SAFETY DATA SHEET

1. Product Information

Product Name: SU 94 Product Class: Paint thinner Product Code: CG0041

2. Composition/Information on Ingredients

Chemical Name	CAS Number	Weight Percent	Occupt. Exposure Limits OSHA PEL ACGIH TLV	Vapor Pressure mm Hg and Temp. F
*Methyl Ethyl Ketone	78-93-3	50	200 ppm 200 pp	om 70 68
Glycol Ether PM Acetate	108-65-6	50	Not Established	3.7 68
3. Physical Data				

Boiling Range (Deg. F): 329°F Vapor Density: Heavier than air Percent Volatile By Volume: 100 Weight Per Gallon (Ibs.): 7.9

Evaporation Rate: Slower than Ether

4. Fire and Explosion Hazard Data

 Flash Point (Deg.F): 138° F
 Lower Explosive Limit: 1.0.
 Extinguishing Media: Foam, CO2, dry chemical, water fog

 OSHA Flammability Classification:
 Combustible liquid, Class II
 Special Firefighting Procedures: Wear a NIOSH/MSHA approved self

 contained breathing apparatus and full protective clothing.
 Use water to keep fire exposed containers cool.
 Water may be ineffective as an extinguishing

 agent.
 Unusual Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or be moved by ventilation to

 ignition sources at locations distant from material handling point.
 Pressure may build up in containers and create an explosion hazard. Never use welding

 or cutting torch on or near drum (even empty).
 Product and reside can ignite explosively.

5. Health Hazard Data

 THIS PRODUCT IS COMBUSTIBLE.
 Effects of Overexposure:
 Eyes: Irritation, burning, tearing and redness.
 Skin: Moderately irritating.

 Ingestion: Abdominal pain, nausea, vomiting and diarrhea.
 Inhalation:
 Headache, nausea and respiratory tract irritant.

 Emergency and First Aid Procedures:
 Eyes: Flush with water for 15 minutes.
 Skin: Remove contaminated clothing, wash skin with soap and water.

 Ingestion: DO NOT induce vomiting.
 Get medical attention immediately.
 Inhalation: Move to fresh air, aid breathing if necessary.

 In all cases, consult a physician for best treatment.
 Chemical listed as carcinogen or potential carcinogen: NTP: No
 IARC: No

 No

6. Reactivity Data

 Stability:
 Product Stable
 Conditions to Avoid: All sources of ignition
 Incompatibility (Materials to avoid): Oxidizing agents, strong acids and bases.

 acids and bases.
 Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, nitrogen oxides and organic compounds.

 Hazardous Polymerization:
 Will not occur.

7. Spill or Leak Procedures

Steps to be taken in case material is released or spilled: Dike spill area. Absorb spill with inert absorbent material. Place in sealed metal containers for proper disposal. Waste Disposal Method: Dispose of in accordance with local, state and federal regulations.

8. Special Protection Information

 Respiratory Protection: Use a NIOSH/MSHA jointly approved respirator
 Ventilation: Use mechanical ventilation

 Protective Gloves: Neoprene or rubber
 Eye Protection: Chemical splash goggles
 Other Protective Equipment: Protective Equipment: Protective Equipment: Protective

 clothing, barrier cream, eve bath, safety shower.
 Barrier cream, eve bath, safety shower.
 Description: Chemical splash goggles
 Description: Chemical splash goggles

9. Special Precautions

Precautions to be taken in handling and storing: Store in dry area. Keep away from open flames and high temperatures. Other precautions: Minimize contact. Avoid breathing vapors. Practice good industrial hygiene and safe working practices.

13. Transportation Information and Regulatory Information

H.M.I.S. Codes:: Health - 3, Flammability - 3, Reactivity - 1